

## WILLOW SPECIFICATION SHEET

### PHYSICAL PROPERTIES

	U.S. Units	Metric Units
Total Weight:	20 oz per linear yd	620.06g per linear meter
Fabric Weight:	2.7 oz per linear yd	83.71g per linear meter
Vinyl Weight:	17.0 oz per linear yd	527.06g per linear meter
Thickness:	0.015 to 0.030 in	0.38 to 0.76mm
Adhesive:	0.3 oz per linear yd	9.03g per linear meter
Fabric:	Highly reflective surface in silver Polyester / vinyl face with non-woven backing	

### PRODUCT PACKAGING

Material Width:	54"
Core Diameter:	3 inch ID Heavy Duty

### SPECIFICATIONS TESTING CERTIFICATION

Federal Specification:	CCC-408-D Type II Class A
WA Specification:	W-101 Type II Class A

### FIRE TESTING

NFPA Life Safety Code 101:	Class A
ASTM-E84 Tunnel Test:	Class A
CAN/ULC-S102.2:	Passed all requirements
NFPA 286 Corner Burn Test:	Class A
BS476 Parts 6 & 7:	Passed all requirements
EU Class Flame (EN 15102):	Passed Class B, s2
ASTM-G21 Specification:	Passed all requirements

Made with Low VOC vinyl  
Tested per CA-1350 Air Quality Standards Cadmium & Lead Free Formulation  
Meets or exceeds requirements for Flame Spread, Smoke Developed, & Flashover