

PALETTE SPECIFICATION SHEET

PHYSICAL PROPERTIES	U.S. Units	Metric Units
Total Weight:	20 oz per linear yd	567 g per linear meter
Vinyl Weight:	17 oz per linear yd	481.94 g per linear meter
Fabric:	Commercial grade printable vinyl wallcovering media Ultra-white embossed vinyl face with laminated fabric backing Backing is poly-cotton woven or polyester/pulp non-woven depending on face emboss	
PRODUCT PACKAGING	Roll Size:	54" x 25 yds, 60" x 50 yds, 75" x 100 yds
	Material Width:	54 inches (+/- 1/4 inches)
	Core Diameter:	3 inch ID Heavy Duty Cardboard Tube
SPECIFICATIONS TESTING CERTIFICATION	Federal Specification:	CCCW-408D Type II, Meets or Exceeds
	WA Specification:	W-101 Type II
FIRE TESTING	ASTM-E84 Tunnel Test:	Class A
	NFPA Life Safety Code 101:	Class A
	NFPA 286 Corner Burn Test:	Class A
	BS476 Parts 6&7:	Passed all requirements
	CAN/ULC-S102.2:	Passed all requirements
	EU Class Flame (EN 15102)	Passed Class B, s2
TYPE II PROPERTIES	Exceeds Machine Direction-warp 50 lbs minimum Breaking Strength Exceeds Cross Machine Direction-fill 55 lbs minimum Breaking Strength Exceeds Machine Direction-warp 25 lbs minimum Tearing Strength Exceeds Cross Machine Direction-fill 25lbs minimum Tearing Strength Cold Crack Resistance at 20°F Heat Aging (7 days at 158°F); does not become stiff, brittle, discolored or show loss of grain ASTM-G21 Mold/Mildew Specifications Passed all requirements	
ENVIRONMENTAL	Low VOC emitting Tested per CA-1350 Air Quality Standards Cadmium & Lead Free Formulation ASTM-G21 Mold/Mildew Specifications Passed all requirements	