

SUMI SPECIFICATION SHEET

PHYSICAL PROPERTIES	U.S. Units	Metric Units
Total Weight:	14 oz per linear yd	435.2g per linear meter
Vinyl Weight:	9.3 oz per linear yd	315.3g per linear meter
Fabric:	Egg-shell white embossed vinyl face laminated with fabric backing Proprietary Polyester/Natural Fiber	
PRODUCT PACKAGING	Material Width:	54 inches (+/- 1/4 inches)
	Core Diameter:	3 inch ID Heavy Duty
SPECIFICATIONS TESTING CERTIFICATION	Federal Specification:	CCCW-408D Type II, Meets or Exceeds
FIRE TESTING	NFPA Life Safety Code 101:	Class A
	ASTM-E84 Tunnel Test:	Class A
	NFPA-101	Passed
ENVIRONMENTAL	PVC & POA (Olefin) Free No plasticizers, phthalates, formaldehyde, chlorine, halogen, heavy metals including cadmium, mercury, lead, or zinc, and no ozone depleting chemicals Minimum 31% post-consumer recycled content Recyclable Breathable* - very high permeability rating of 66 Perms based on ASTM E96 Procedure B (Wet Cup) Made with 10% water based adhesive systems No harmful off gassing Low VOC emitting Tested per CA-1350 Air Quality Standards Meets or exceeds requirements for Flame Spread, Smoke Developed, & Flashover	
LEEDS ELIGIBILITY	Can contribute up to 6 LEEDs credits MR Credit 4.1 Recycled content 10% MR Credit 4.2 Recycled content 20% Conditionally: MR Credit 2.1 Contribution to project recycling program MR Credit 2.2 Contribution to project recycling program MR Credit 5.1 Manufactured local to the new construction (CA) EQ Credit 4.1 When mounted with use of low emitting adhesives Note: All LEED credits are based on the total construction of a building. Adobe offers up to a 50% advantage over competitive products for achieving MR Credit 4.1 and MR Credit 4.2 because of its higher percentage of post-consumer recycled materials.	