

TERRA TYPE II SPECIFICATION SHEET

Colorways: Aether, Astra, Comet, Matter, Nitre

PHYSICAL PROPERTIES	U.S. Units	Metric Units
Total Weight:	14 oz per linear yd	435.2g per linear meter
Material Weight:	9.3 oz per linear yd	315.3g per linear meter
Fabric:	Egg-shell white embossed face laminated with fabric backing Proprietary Polyester/Natural Fiber	
PRODUCT PACKAGING	Roll Size:	54 inches
	Material Width:	52 inch wide panels on 54 inch wide material
	Core Diameter:	3 inch ID Heavy Duty
SPECIFICATIONS TESTING CERTIFICATION	Federal Specification:	CCCW-408D Type II, Meets or Exceeds
FIRE TESTING	NFPA Life Safety Code 101:	Class A
	ASTM-E84 Tunnel Test:	Class A
	NFPA-101	Passed
ENVIRONMENTAL	PVC & POA (Olefin) Free No plasticizers, phthalates, formaldehyde, chlorine, halogen, heavy metals including cadmium, mercury, lead, or zinc, and no ozone depleting chemicals Minimum 31% post-consumer recycled content Recyclable Breathable* - very high permeability rating of 66 Perms based on ASTM E96 Procedure B (Wet Cup) Made with 10% water based adhesive systems No harmful off gassing Low VOC emitting Tested per CA-1350 Air Quality Standards Meets or exceeds requirements for Flame Spread, Smoke Developed, & Flashover	
LEEDS ELIGIBILITY	Can contribute up to 6 LEEDs credits MR Credit 4.1 Recycled content 10% MR Credit 4.2 Recycled content 20% Conditionally: MR Credit 2.1 Contribution to project recycling program MR Credit 2.2 Contribution to project recycling program MR Credit 5.1 Manufactured local to the new construction (CA) EQ Credit 4.1 When mounted with use of low emitting adhesives Note: All LEED credits are based on the total construction of a building. Adobe offers up to a 50% advantage over competitive products for achieving MR Credit 4.1 and MR Credit 4.2 because of its higher percentage of post-consumer recycled materials.	

TERRA ALUM & TERRA ELEMENT [TYPE II] SPECIFICATION SHEET

PHYSICAL PROPERTIES		U.S. Units	Metric Units
	Total Weight:	20 oz per linear yd	620.06g per linear meter
	Fabric Weight:	2.7 oz per linear yd	83.71g per linear meter
	Vinyl Weight:	17.0 oz per linear yd	527.06g per linear meter
	Thickness:	0.015 to 0.030 in	0.38 to 0.76mm
	Adhesive:	0.3 oz per linear yd	9.03g per linear meter
	Fabric:	Highly reflective surface in silver Polyester/ vinyl face with non-woven backing	
PRODUCT PACKAGING	Material Width:	30 inch wide material on 27 inch maximum panel width	
	Core Diameter:	3 inch ID Heavy Duty	
SPECIFICATIONS TESTING CERTIFICATION	Federal Specification:	CCC-408-D Type II Class A	
	WA Speciafication:	W-101 Type II Class A	
FIRE TESTING	NFPA Life Safety Code 101:	Class A	
	ASTM-E84 Tunnel Test:	Class A	
	CAN/ULC-S102.2:	Passed all requirements	
	NFPA 286 Corner Burn Test:	Class A	
	BS476 Parts 6 & 7:	Passed all requirements	
	EU Class Flame (EN 15102):	Passed Class B, s2	
	ASTM-G21 Specification:	Passed all requirements	
	Made with Low VOC vinyl		
	Tested per CA-1350 Air Quality Standards Cadmuim & Lead Free Formulation		
	Meets or exceeds requirements for Flame Spread, Smoke Developed, & Flashover		