

## NOIR TYPE II SPECIFICATION SHEET

### PHYSICAL PROPERTIES

|               |  |
|---------------|--|
| Total Weight: | 18 oz per linear yd (480g per linear meter)                                      |
| Composition:  | 100% TPO (Thermoplastic Olefin) face with nonwoven polyester / cellulose backing |
| Abrasion:     | Taber Abrasion - Grade 5   |

### PRODUCT PACKAGING

|                 |  |
|-----------------|--|
| Material Width: | 54 inches; usable width 52 inches (130 cm) |
| Core Diameter:  | 3 inch ID Heavy Duty                       |

### SPECIFICATIONS TESTING CERTIFICATION

|                        |                           |
|------------------------|---------------------------|
| Federal Specification: | CCC-408-D Type II Class A |
| WA Speciafication:     | W-101 Type II Class A     |

### TESTING

|                                |                    |
|--------------------------------|--------------------|
| ASTM-E84 Tunnel Test:          | Class A            |
| NFPA 286 Corner Burn Test:     | Class A            |
| EU Class Flame (EN 15102):     | Passed Class B, s2 |
| ASTM-D751 (Breaking Strength): | 83 × 60            |
| ASTM-D751 (Tear Strength):     | 47 × 48            |

PVC Free  
Phthalate Free Substrate  
Nonwoven backing is made from 50% post-consumer recycled content  
TPO face contains a minimum of 14% post-consumer recycled glass